

Powerful Slimline Roller Door Opener for Residential Rolling Garage Doors

Rated door area	12.5m ²
Pulling force	500N
Motor	DC



Design appeal mixed with modern practicality for doors up to 12.5m²

Soft Start/Stop:

The MR650 is equipped with Chamberlain Soft Start/Stop technology. This is designed to ensure smooth and quiet door operation

Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation

Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door

Three Channel Mini-Transmitter (two included):

A three channel mini transmitter with rolling code technology can control up to three different doors or gates

Wireless Wall Button (included):

Wireless push button equipped with rolling code technology for remote operation in the garage or home - designed to look like a conventional domestic switch

Manual Release:

In case of power failure you can simply activate the manual release to open your garage door

Accessories:

A wide range of wireless and other add-on accessories is available for this opener.

Warranty:

The MR650 comes with a two year general warranty

Key Features	Optional Accessories	Specifications
<ul style="list-style-type: none"> Soft Start/Stop operation Auto safety function Auto force sensing Two 3 channel mini-transmitters Wireless wall button Rolling code technology with Peak Detect Up to 64 memory registers Ultra-bright LED lighting Manual release handle Minimum side room 45mm 	<ul style="list-style-type: none"> IR Beams Motion-detecting control panel Keyed manual release Single channel transmitter 3 or 4 channel mini-transmitters Fingerprint keyless entry system Wireless keypad 	<ul style="list-style-type: none"> 24V DC motor with thermal overload protection Input voltage: 240V AC Rated door area 12.5m² Pulling force: 500N 433.92 MHz AM radio with rolling code Peak Detect receiver