

## The "All Rounder" Sectional & Tilt Garage Door Opener for Single & Heavy Double Door Garages

Rated door area	15.5m <sup>2</sup>
Pulling force	800N
Motor	AC
Drive	Chain/Pole



The 5580 platform is the best selling garage door opener in the world!

### Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation.

### Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door.

### Manual Release:

In case of power failure you can simply activate the manual release to open your garage door.

### Wireless Wall Button (included):

Wireless push button equipped with rolling code technology for remote operation in the garage or home.

### Three Channel Mini Transmitter (two included):

A three channel mini-transmitter with rolling code technology can control up to three different doors or gates.

### 24V Accessory Output:

Allows easy installation of wired accessory devices directly to the opener's power supply terminals.

### Dual Speed:

The MT5580P can be configured to run faster or slower. Ideal for older one-piece doors.

### Warranty:

The MT5580P comes with a two year general warranty and a five year warranty on the motor.

Key Features	Optional Accessories	Specifications
<ul style="list-style-type: none"> <li>• Auto safety function</li> <li>• Auto force sensing</li> <li>• One piece pole and chain drive system</li> <li>• Two 3 channel mini-transmitters</li> <li>• Wireless wall button CM128</li> <li>• Rolling code technology</li> <li>• Up to 8 memory registers</li> <li>• Manual release handle</li> <li>• Courtesy light</li> <li>• Multiple mounting points</li> <li>• 24V accessory output</li> <li>• 5 year motor warranty</li> </ul>	<ul style="list-style-type: none"> <li>• Single channel transmitter</li> <li>• 3 or 4 channel mini-transmitters</li> <li>• Safety beam sensors</li> <li>• Keyed manual release</li> <li>• Add on receivers</li> <li>• Motion detecting control panel</li> <li>• Fingerprint keyless entry system</li> <li>• Noise reducing pads</li> </ul>	<ul style="list-style-type: none"> <li>• 240V AC motor with thermal overload protection</li> <li>• Input voltage: 240V AC</li> <li>• Rated door area 15.5m<sup>2</sup></li> <li>• Lifting capacity: 800N</li> <li>• 433.92 MHz AM radio with rolling code</li> <li>• Dual speed sprocket</li> </ul>